

# SPRAY CLEANER™

## Spray - Wipe - Mop, Fast Acting Non-Flammable Cleaner

**Wipe off dirt, wax, oil, grease, crayon & soap scum easily and rapidly.**

**WENCO® SPRAY CLEANER™ INDUSTRIAL PLANTS USES** - Safely cleans grease from industrial equipment and machinery. Whisks grime from windows. Especially good for greasy concrete floors. Cleans oil and grease from small parts. Degreasing metals before magnafluxing.

**COMMERCIAL ESTABLISHMENTS** - Keeps stoves and hoods gleaming and sanitary. Removes grease and dirt from all kitchen surfaces, ventilating and air-filtering systems, linoleum, asphalt tile and terrazzo floors. Makes chromium and nickel glisten like new.

### DIRECTIONS FOR USE

**CONCRETE FLOORS:** Use 1 part cleaner with 1 part water to remove oil, grease, wax and extremely heavy dirt. Thoroughly rinse with clear water.

**FLOORS and PAINTED WALLS:** Use on OIL BASE paints only. Add 1 part of cleaner to 30 parts of water. Rinse with clear water and wipe dry.

**WAX REMOVAL on ASPHALT, RUBBER and LINOLEUM TILE:** Use 1 part cleaner to 8 parts of water to remove buildup of wax and heavy dirt. For any general type of cleaning, use 1 part cleaner to 20 parts water. Rinse with clear water and mop dry.

**KITCHEN AREA:** To remove baked carbon from inside of oven doors, use full strength. If necessary, lightly scour with steel wool. For cleaning grease stained walls, ceilings and tile, use a solution of 1 part cleaner to 8 parts water. Thoroughly rinse with clear water and wipe dry.

**ALUMINUM and STAINLESS STEEL:** Add 1 part cleaner to 10 parts water and wipe off with a clean damp cloth.

### TECHNICAL PROPERTIES

Form.....	Liquid
Color.....	Blue
pH Concentrate.....	12.9 - 13.2
pH 1% Solution.....	10.2
Specific Gravity @ 75°F.....	1.04
Density @ 75°F.....	8.65 lbs Per Gallon
Viscosity @ 75°F.....	Thin
Flash Point (COC).....	None
Solvents.....	2-Butoxyethanol
Rinsability.....	Good
Foaming.....	Moderate

### AVAILABLE SIZES

- ✓ **4x1 Gallon Case**  
Bottles Contain 25% PCR  
Carton Contains 55% PCR
- ✓ **55 Gallon Drum**  
Reconditioned, Reused

<b>1</b>	<b>HEALTH</b>
<b>0</b>	<b>FLAMMABILITY</b>
<b>0</b>	<b>REACTIVITY</b>
<b>B</b>	<b>PERSONAL PROTECTION</b>

MSDS Available 24 / 7 / 365  
[msds.walterenelson.com](http://msds.walterenelson.com)



**SPRAY - Wipe - Mop, Fast Acting Non-Flammable Cleaner**

# SPRAY-CLEANER™



**WENCO** Brand  
CLEANING SYSTEMS



**WALTER E. NELSON COMPANY**  
(800) 929-2141 • [www.walterenelson.com](http://www.walterenelson.com)





are irritating to skin. Prolonged exposure may burn the skin.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Redness, drying of skin, or other signs of irritation or contact dermatitis. May result in primary irritant dermatitis. ETHYLENE GLYCOL MONOBUTYL ETHER is readily absorbed through the skin causing headaches, nausea, vomiting, and diarrhea.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapors, mists, and liquid are irritating to the mouth and throat. Swallowing the liquid burns the tissues, and may cause severe abdominal pain, nausea, and vomiting. May cause red blood cell hemolysis, liver and kidney injury.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Repeated overexposure may cause damage to the liver, kidneys, and red blood cells. May be very irritating to the eyes on contact. Inhalation of vapors, or mists may cause varying degrees of damage to the affected tissues and also increasing susceptibility to respiratory illness.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**

The components of this product are not considered to be carcinogens by the National Toxicology Program, the International Agency for Research on Cancer, or the Occupational Safety and Health Administration.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Persons with pre-existing dermatitis may be more susceptible to the effects of this material.

**EMERGENCY AND FIRST AID PROCEDURES**

INHALATION - Remove to fresh air. Give artificial respiration if not breathing. EYES - Flush immediately with lots of running water for at least 15 minutes holding eye lids open. GET MEDICAL ATTENTION. SKIN - Immediately flush skin with lots of running water for at least 15 minutes. Remove contaminated clothing and shoes. INGESTION - Drink 1 to 8 glasses of water to dilute. DO NOT INDUCE VOMITING. Consult a physician or poison control center immediately. Treat symptomatically. Do not give anything by mouth to an unconscious or convulsing person.

**===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====**  
**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

For small spills dilute with water, mop or wipe up and contain. For large spills, contain by diking with absorbant material and carefully neutralize with a mild acid. Keep material out of sewers, storm drains, surface waters, and soil.

**WASTE DISPOSAL METHOD**

Comply with all applicable governmental regulations on spill reporting, handling and disposal of waste. Dispose of contaminated product and materials used in clean up in a manner approved for this material and the contaminant. Consult appropriate Federal, State and Local regulatory agencies to ascertain proper disposal procedures and comply with them.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store in a dry, well ventilated place away from incompatible materials. Keep container tightly closed when not in use. Store at temperatures above the solutions freezing point to remain liquid. Do not use pressure to empty container.

**OTHER PRECAUTIONS**

Empty containers usually still hold residues of material and vapors. These must be considered hazardous and disposed of in accordance with proper handling procedures prescribed for hazardous chemicals. When mixing with water, always add this product to water and stir.

**===== SECTION VIII - CONTROL MEASURES =====**  
**RESPIRATORY PROTECTION**

In the absence of adequate ventilation an approved respirator may be required.

**VENTILATION**

Be sure to provide adequate ventilation in all working areas at all time. In general, health problems could result from repeated and prolonged exposure to chemical vapors.

**PROTECTIVE GLOVES**

M A T E R I A L   S A F E T Y   D A T A   S H E E T

WEN SPRAY CLEANER 4X1 CASE

Page: 3

8/8/2008

---

Wear resistant gloves such as polyethylene or rubber.

**EYE PROTECTION**

Chemical splash goggles should be worn during application of this product.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Where gross eye and skin contact may occur use and wear appropriate clothing, rubber boots with pants on the outside, and rubber gloves.

**WORK/HYGIENIC PRACTICES**

Standard hygienic practices must be observed when handling all chemicals.

**===== SECTION IX - DISCLAIMER =====**

Information contained herein is furnished without warranty of any kind. Employees should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and for the safety and health of employees.